

Winchmax HYDRAULIC WINCH 20000lb



12v

20,000lb (9.0 tonnes) straight line pull

Massive Ultra Tough three stage gearbox

Sliding Ring Gear Free wheel clutch

New upgrade; gearbox cover cylinder is now machined billet steel for ultimate protection from accidental impact damage

Super heavy duty 4 roller fairlead

The solenoid operated main hydraulic valve supplied with this winch is compatible with our range of wireless remote controls. See separate listing for details.

CE Certified & Built to ISO9001 Quality Management System Requirements.

Single line rated pull	20000lb(9072kg)
Motor	Hydraulic
Control	Remote Switch, 12ft(3.7m) lead , In and Out
Gear train	3 Stage Planetary
Gear reduction ratio	358:1
Clutch	Sliding Ring Gear
Braking Action	Automatic
Drum size	Diameter 88mm Length 222mm
Cable	26m (85ft) of 12mm diameter
Fairlead	4-Way Roller Fairlead
Flow	50-60 L/min
Pressure	10.8Mpa (108 Bar)
Finish	Orange / Black
Weight	GW 65KG
Overall Dimensions (LxWxH)	548x196x249mm
Mounting Bolt Pattern	10.00"±0.015"x4.50"±0.010"(254x114.3mm)
Pressure Hose Connections	18mm/1.5mm
No Load Line Speed	6.5m/min (21.3 ft/min)