

# Winchmax 13,500lb 12v Dyneema SK75 Synthetic Rope



28m UHMWPE 11mm / 12 strand synthetic rope

Super powerful 12V 6hp series wound electric motor

Power In / out removable big grip extra long (4.5m) corded handheld remote control unit

Tough three stage gearbox

Albright type solenoids/Free wheel clutch

Super heavy duty 4 roller fairlead

CE Certified & Built to ISO9001 Quality Management System Requirements.



Single line rated pull	13000lb(5700kg)
Motor	6.0hp/4.5kw, Series Wound
Control	Remote Switch, Extra long 4.5m lead , In and Out PLUS Twin Handset Wireless Remote
Gear train	3 Stage Planetary
Gear reduction ratio	266:01:00
Clutch	Sliding Ring Gear
Braking Action	Automatic In The Drum
Drum size	Diameter 64mm (2.52")Length 224mm(8.82")
Cable	28M UHMWPE 12 Strand Synthetic Rope
Fairlead	Aluminium Hawse
Battery	Recommended 650CCA minimum for winching
Battery Leads	2 gauge, 1.83m (72") 35mmsq - 6.5mm Diameter
Finish	Black - Low Light, Signature Textured, Powder Coat
Weight	GW 43KG (95lb)
Overall Dimensions (LxWxH)	536x160x218mm (21.3"x6.3"x8.6")
Mounting Bolt Pattern	10.00"±0.015"x4.50"±0.010"(254x114.3mm)
Motor Current	65-400A
No Load Line Speed	6.5m/min (21.3 ft/min)