

Winchmax 17,500lb 12v Electric Winch

17,500lb (almost 8 tonnes) straight line pull

Latest technology long range wireless remote

Super powerful 12v 6.6hp series wound electric motor

Power In / Out big grip handheld unit can be used wirelessly or with lead.

Massive Ultra Tough three stage gearbox

Upgraded recovery solenoids

Sliding Ring Gear Free wheel clutch

New upgrade; gearbox cover cylinder is now machined billet steel for ultimate protection from accidental impact damage

CNC billet aluminium hawse fairlead

| | | | | | | | |
|----------------------|---------------|---------|------|-------|-------|-------|-------|
| Line Pull | lbs | No Load | 6000 | 10000 | 12000 | 14000 | 17500 |
| | kg | No Load | 2721 | 4536 | 5454 | 6363 | 7937 |
| Line Speed | ft/min | 23.62 | 9.18 | 5.90 | 4.92 | 4.26 | 2.95 |
| | m/min | 7.2 | 2.8 | 1.8 | 1.5 | 1.3 | 0.9 |
| Motor Current | Amps | 71 | 200 | 300 | 350 | 395 | 450 |

| | | | | | |
|----------------------------------|-----|----------|----------|----------|----------|
| Layers Of Cable | | 1 | 2 | 3 | 4 |
| Rated Line pull per layer | lbs | 17500 | 15225 | 13246 | 11524 |
| | kg | 7955 | 6920 | 6021 | 5238 |
| Cumulative cable capacity | ft | 19.68 | 45.92 | 75.44 | 85.28 |
| | m | 6 | 14 | 23 | 26 |

12v



| | | | |
|-----------------------------|---|-------------------------------|---|
| Waterproof: | IP68 Rating | Fairlead: | Aluminium Hawse Integrated wireless and wired remote Included |
| Rated Max Line Pull: | 17,500Lbs (7,954kgs) single-line | Remote Control: | Included 750CCA |
| Motor: | 6.6hp Series Wound | Recommended Battery: | Minimum for Winching 30mm2 x 72" (1.83m) |
| Control: | Remote Switch, 12' (3.7m) lead | Battery Leads: | 30mm2 x 72" (1.83m) |
| Gear Train: | 3-Stage Planetary | Finish: | Textured Orange |
| Gear Ratio: | 430:1 | Weight: | 130.0Lbs (60.0Kgs) |
| Clutch: | Sliding Ring Gear | Mounting Bolt Pattern: | 10.0" (254mm) x 4.50" (114mm) |
| Brake: | Automatic Out-Of-Drum Diameter 3.45" (88mm) | Overall Dimension | L 562 x W 194 x H248.3 mm |
| Drum Size: | (88mm) Length 10.0" (254mm) | Rope: | UHMWPE 24m x 13mm Diameter |